

ENTRY SEAL DUCT PLUGS


Termination plugs for conduits and innerducts

KEY FEATURES


- Water and air resistant
- Installation around in-place cables
- Excellent conduit or cable support
- Made from recyclable materials
- Stainless steel fasteners
- Easy to install
- Protects and organizes
- Corrosion proof
- Ideal for manholes, buildings, and cabinets
- Fast lead times



Simplex



Triplex



Quadplex



Split duct plugs that organize and anchor wires, cables, and conduit within raceway systems

Wedge Seal™ Entry Seal Duct Plug simplex, triplex and quadplex effectively organize, anchor, and seal subducts, conduits, and cables. Utilizing a split design, these seals can be installed almost anywhere along a cable network. They are perfect for retrofits.

Manufactured from a combination of high-impact plastic components and pliable, yet durable, gaskets. These Entry Seal Duct Plugs prevent the incursion of water and sedimentation into costly duct banks, raceway systems, and fiber networks while also confining potential problems like dangerous vapors to their source.

For a long lasting and professional installation these seals use stainless steel fasteners and can be installed with widely available hand-tools.

Many of our sizes are JackMoon® cross-referenced for a seamless part number conversion.

Available in many configurations. For cross-referencing or custom sizes please contact us for more information.

CABLE ACCESSORIES

L I M I T E D

SPECIFICATIONS

PRODUCT NUMBER	JACKMOON CROSS-REFERENCE NO	EACH SIZE (IN)	EACH SIZE (MM)	CONDUIT I.D. (IN)	CONDUIT I.D. (MM)	PORT DIAM RANGE (IN)	PORT DIAM RANGE (MM)
SIMPLEX							
7140-100	JM-SIM-40S118S*	4"	100	3.95"-4.15"	100.33-105.41	0.98"-1.02"	24.89-25.91
7140-105	JM-SIM-40S118S*	4"	100	3.95"-4.15"	100.33-105.41	1.03"-1.07"	26.16-27.18
7140-110	JM-SIM-40S118S*	4"	100	3.95"-4.15"	100.33-105.41	1.08"-1.12"	27.43-28.45
7140-115	JM-SIM-40S118S*	4"	100	3.95"-4.15"	100.33-105.41	1.13"-1.17"	28.70-29.72
7140-120	JM-SIM-40S136S*	4"	100	3.95"-4.15"	100.33-105.41	1.18"-1.22"	29.97-30.99
7140-125	JM-SIM-40S136S*	4"	100	3.95"-4.15"	100.33-105.41	1.23"-1.27"	31.24-32.26
7140-130	JM-SIM-40S136S*	4"	100	3.95"-4.15"	100.33-105.41	1.28"-1.32"	32.51-33.53
7140-135	JM-SIM-40S136S*	4"	100	3.95"-4.15"	100.33-105.41	1.33"-1.37"	33.78-34.80
7140-140	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.38"-1.42"	35.05-36.07
7140-145	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.43"-1.47"	36.32-37.34
7140-150	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.48"-1.52"	37.59-38.61
7140-155	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.53"-1.57"	38.86-39.88
7140-160	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.58"-1.62"	40.13-41.15
7140-165	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.63"-1.67"	41.40-42.42
7140-170	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.68"-1.72"	42.67-43.69
7140-175	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.73"-1.77"	43.94-44.96
7140-180	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.78"-1.82"	45.21-46.23
7140-185	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.83"-1.87"	46.48-47.50
7140-190	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.88"-1.92"	47.75-48.77
7140-195	JM-SIM-40S196SB*	4"	100	3.95"-4.15"	100.33-105.41	1.93"-1.97"	49.02-50.04
7140-200		4"	100	3.95"-4.15"	100.33-105.41	1.98"-2.02"	50.30-51.05
7140-205	JM-SIM-40S216S*	4"	100	3.95"-4.15"	100.33-105.41	2.03"-2.07"	51.56-52.58
7140-210	JM-SIM-40S216S*	4"	100	3.95"-4.15"	100.33-105.41	2.08"-2.12"	52.83-53.85
7140-215	JM-SIM-40S216S*	4"	100	3.95"-4.15"	100.33-105.41	2.13"-2.17"	54.10-55.12
7140-220		4"	100	3.95"-4.15"	100.33-105.41	2.18"-2.22"	55.37-56.39
7140-225	JM-SIM-40S236S*	4"	100	3.95"-4.15"	100.33-105.41	2.23"-2.27"	56.64-57.66
7140-230	JM-SIM-40S236S*	4"	100	3.95"-4.15"	100.33-105.41	2.28"-2.32"	57.91-58.93
7140-235	JM-SIM-40S236S*	4"	100	3.95"-4.15"	100.33-105.41	2.33"-2.37"	59.18-60.20
7140-240		4"	100	3.95"-4.15"	100.33-105.41	2.38"-2.42"	60.45-61.49
7140-245		4"	100	3.95"-4.15"	100.33-105.41	2.43"-2.47"	61.72-62.74
TRIPLEX							
7340-075		4"	100	3.95"-4.15"	100.33-105.41	0.73"-0.77"	18.54-19.56
7340-080		4"	100	3.95"-4.15"	100.33-105.41	0.78"-0.82"	19.81-20.83
7340-085		4"	100	3.95"-4.15"	100.33-105.41	0.83"-0.87"	21.08-22.10
7340-090		4"	100	3.95"-4.15"	100.33-105.41	0.88"-0.92"	22.35-23.37
7340-095		4"	100	3.95"-4.15"	100.33-105.41	0.93"-0.97"	23.62-24.64
7340-100		4"	100	3.95"-4.15"	100.33-105.41	0.98"-1.02"	24.89-25.91
7340-105	JM-TRI-40B122SG*	4"	100	3.95"-4.15"	100.33-105.41	1.03"-1.07"	26.16-27.18
7340-110	JM-TRI-40B122SG*	4"	100	3.95"-4.15"	100.33-105.41	1.08"-1.12"	27.43-28.45

CABLE ACCESSORIES

L I M I T E D

SPECIFICATIONS

PRODUCT NUMBER	JACKMOON CROSS-REFERENCE NO	EACH SIZE (IN)	EACH SIZE (MM)	CONDUIT I.D. (IN)	CONDUIT I.D. (MM)	PORT DIAM RANGE (IN)	PORT DIAM RANGE (MM)
7340-115	JM-TRI-40B122SG*	4"	100	3.95"-4.15"	100.33-105.41	1.13"-1.17"	28.70-29.72
7340-120	JM-TRI-40B122SG* / JM-TRI-40B136S*	4"	100	3.95"-4.15"	100.33-105.41	1.18"-1.22"	29.97-30.99
7340-125	JM-TRI-40B136S*	4"	100	3.95"-4.15"	100.33-105.41	1.23"-1.27"	31.24-32.26
7340-130	JM-TRI-40B136S* / JM-TRI-40B142SG*	4"	100	3.95"-4.15"	100.33-105.41	1.28"-1.32"	32.51-33.53
7340-135	JM-TRI-40B136S* / JM-TRI-40B142SG* / JM-TRI-40B150SG*	4"	100	3.95"-4.15"	100.33-105.41	1.33"-1.37"	33.78-34.80
7340-140	JM-TRI-40B150SG*	4"	100	3.95"-4.15"	100.33-105.41	1.38"-1.42"	35.05-36.07
7340-145	JM-TRI-40B150SG*	4"	100	3.95"-4.15"	100.33-105.41	1.43"-1.47"	36.32-37.34
7340-150	JM-TRI-40B167S*	4"	100	3.95"-4.15"	100.33-105.41	1.48"-1.52"	37.59-38.61
7340-155	JM-TRI-40B167S*	4"	100	3.95"-4.15"	100.33-105.41	1.53"-1.57"	38.86-39.88
7340-160	JM-TRI-40B167S*	4"	100	3.95"-4.15"	100.33-105.41	1.58"-1.62"	40.13-41.15
7340-165	JM-TRI-40B167S*	4"	100	3.95"-4.15"	100.33-105.41	1.63"-1.67"	41.40-42.42
7340-XXX		4"	100	3.95"-4.15"	100.33-105.41	CUSTOM	CUSTOM
7350-075		5"	125	4.95"-5.15"	125.73-130.81	0.73"-0.77"	18.54-19.56
7350-080		5"	125	4.95"-5.15"	125.73-130.81	0.78"-0.82"	19.81-20.83
7350-085		5"	125	4.95"-5.15"	125.73-130.81	0.83"-0.87"	21.08-22.10
7350-090		5"	125	4.95"-5.15"	125.73-130.81	0.88"-0.92"	22.35-23.37
7350-095		5"	125	4.95"-5.15"	125.73-130.81	0.93"-0.97"	23.62-24.64
7350-100		5"	125	4.95"-5.15"	125.73-130.81	0.98"-1.02"	24.89-25.91
7350-105		5"	125	4.95"-5.15"	125.73-130.81	1.03"-1.07"	26.16-27.18
7350-110		5"	125	4.95"-5.15"	125.73-130.81	1.08"-1.12"	27.43-28.45
7350-115		5"	125	4.95"-5.15"	125.73-130.81	1.13"-1.17"	28.70-29.72
7350-120		5"	125	4.95"-5.15"	125.73-130.81	1.18"-1.22"	29.97-30.99
7350-125		5"	125	4.95"-5.15"	125.73-130.81	1.23"-1.27"	31.24-32.26
7350-130		5"	125	4.95"-5.15"	125.73-130.81	1.28"-1.32"	32.51-33.53
7350-135		5"	125	4.95"-5.15"	125.73-130.81	1.33"-1.37"	33.78-34.80
7350-140		5"	125	4.95"-5.15"	125.73-130.81	1.38"-1.42"	35.05-36.07
7350-145		5"	125	4.95"-5.15"	125.73-130.81	1.43"-1.47"	36.32-37.34
7350-150	JM-TRI-50B167SG*	5"	125	4.95"-5.15"	125.73-130.81	1.48"-1.52"	37.59-38.61
7350-155	JM-TRI-50B167SG*	5"	125	4.95"-5.15"	125.73-130.81	1.53"-1.57"	38.86-39.88
7350-160	JM-TRI-50B167SG*	5"	125	4.95"-5.15"	125.73-130.81	1.58"-1.62"	40.13-41.15
7350-165	JM-TRI-50B167SG* / JM-TRI-50B177SG*	5"	125	4.95"-5.15"	125.73-130.81	1.63"-1.67"	41.40-42.42
7350-170	JM-TRI-50B177SG*	5"	125	4.95"-5.15"	125.73-130.81	1.68"-1.72"	42.67-43.69
7350-175	JM-TRI-50B177SG*	5"	125	4.95"-5.15"	125.73-130.81	1.73"-1.77"	43.94-44.96
7350-180		5"	125	4.95"-5.15"	125.73-130.81	1.78"-1.82"	45.21-46.23
7350-XXX		5"	125	4.95"-5.15"	125.73-130.81	CUSTOM	CUSTOM

CABLE ACCESSORIES

L I M I T E D

SPECIFICATIONS

PRODUCT NUMBER	JACKMOON CROSS-REFERENCE NO	EACH SIZE (IN)	EACH SIZE (MM)	CONDUIT I.D. (IN)	CONDUIT I.D. (MM)	PORT DIAM RANGE (IN)	PORT DIAM RANGE (MM)
7360-075		6"	150	5.96"-6.15"	151.38-156.21	0.73"-0.77"	18.54-19.56
7360-080		6"	150	5.96"-6.15"	151.38-156.21	0.78"-0.82"	19.81-20.83
7360-085		6"	150	5.96"-6.15"	151.38-156.21	0.83"-0.87"	21.08-22.10
7360-090		6"	150	5.96"-6.15"	151.38-156.21	0.88"-0.92"	22.35-23.37
7360-095		6"	150	5.96"-6.15"	151.38-156.21	0.93"-0.97"	23.62-24.64
7360-100		6"	150	5.96"-6.15"	151.38-156.21	0.98"-1.02"	24.89-25.91
7360-105		6"	150	5.96"-6.15"	151.38-156.21	1.03"-1.07"	26.16-27.18
7360-110		6"	150	5.96"-6.15"	151.38-156.21	1.08"-1.12"	27.43-28.45
7360-115		6"	150	5.96"-6.15"	151.38-156.21	1.13"-1.17"	28.70-29.72
7360-120	JM-TRI-60B136SG*	6"	150	5.96"-6.15"	151.38-156.21	1.18"-1.22"	29.97-30.99
7360-125	JM-TRI-60B136SG*	6"	150	5.96"-6.15"	151.38-156.21	1.23"-1.27"	31.24-32.26
7360-130	JM-TRI-60B136SG*	6"	150	5.96"-6.15"	151.38-156.21	1.28"-1.32"	32.51-33.53
7360-135	JM-TRI-60B136SG*	6"	150	5.96"-6.15"	151.38-156.21	1.33"-1.37"	33.78-34.80
7360-140		6"	150	5.96"-6.15"	151.38-156.21	1.38"-1.42"	35.05-36.07
7360-145		6"	150	5.96"-6.15"	151.38-156.21	1.43"-1.47"	36.32-37.34
7360-150	JM-TRI-60B167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.48"-1.52"	37.59-38.61
7360-155	JM-TRI-60B167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.53"-1.57"	38.86-39.88
7360-160	JM-TRI-60B167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.58"-1.62"	40.13-41.15
7360-165	JM-TRI-60B167SG* / JM-TRI-60B177SG*	6"	150	5.96"-6.15"	151.38-156.21	1.63"-1.67"	41.40-42.42
7360-170	JM-TRI-60B177SG*	6"	150	5.96"-6.15"	151.38-156.21	1.68"-1.72"	42.67-43.69
7360-175	JM-TRI-60B177SG*	6"	150	5.96"-6.15"	151.38-156.21	1.73"-1.77"	43.94-44.96
7360-180		6"	150	5.96"-6.15"	151.38-156.21	1.78"-1.82"	45.21-46.23
7360-185	JM-TRI-60B196SG*	6"	150	5.96"-6.15"	151.38-156.21	1.83"-1.87"	46.48-47.50
7360-190	JM-TRI-60B196SG*	6"	150	5.96"-6.15"	151.38-156.21	1.88"-1.92"	47.75-48.77
7360-195	JM-TRI-60B196SG*	6"	150	5.96"-6.15"	151.38-156.21	1.93"-1.97"	49.02-50.04
7360-XXX		6"	150	5.96"-6.15"	151.38-156.21	CUSTOM	CUSTOM
7380-240		8"	200	7.74"-7.94"	196.60-201.68	2.38"-2.42"	60.45-61.49
7380-245		8"	200	7.74"-7.94"	196.60-201.68	2.43"-2.47"	61.72-62.74
7380-250		8"	200	7.74"-7.94"	196.60-201.68	2.48"-2.52"	62.99-64.01
7380-255		8"	200	7.74"-7.94"	196.60-201.68	2.53"-2.57"	64.26-65.28
7380-260		8"	200	7.74"-7.94"	196.60-201.68	2.58"-2.62"	65.53-66.55
7380-265		8"	200	7.74"-7.94"	196.60-201.68	2.63"-2.67"	66.80-67.82
7380-270		8"	200	7.74"-7.94"	196.60-201.68	2.68"-2.72"	68.07-69.01
7380-XXX		8"	200	7.74"-7.94"	196.60-201.68	CUSTOM	CUSTOM
QUADPLEX							
7440-075		4"	100	3.95"-4.15"	100.33-105.41	0.73"-0.77"	18.54-19.56
7440-080		4"	100	3.95"-4.15"	100.33-105.41	0.78"-0.82"	19.81-20.83
7440-085		4"	100	3.95"-4.15"	100.33-105.41	0.83"-0.87"	21.08-22.10
7440-090		4"	100	3.95"-4.15"	100.33-105.41	0.88"-0.92"	22.35-23.37

CABLE ACCESSORIES

L I M I T E D

SPECIFICATIONS

PRODUCT NUMBER	JACKMOON CROSS-REFERENCE NO	EACH SIZE (IN)	EACH SIZE (MM)	CONDUIT I.D. (IN)	CONDUIT I.D. (MM)	PORT DIAM RANGE (IN)	PORT DIAM RANGE (MM)
7440-095		4"	100	3.95"-4.15"	100.33-105.41	0.93"-0.97"	23.62-24.64
7440-100		4"	100	3.95"-4.15"	100.33-105.41	0.98"-1.02"	24.89-25.91
7440-105		4"	100	3.95"-4.15"	100.33-105.41	1.03"-1.07"	26.16-27.18
7440-110		4"	100	3.95"-4.15"	100.33-105.41	1.08"-1.12"	27.43-28.45
7440-115		4"	100	3.95"-4.15"	100.33-105.41	1.13"-1.17"	28.70-29.72
7440-120	JM-QUA-40Q136SG*	4"	100	3.95"-4.15"	100.33-105.41	1.18"-1.22"	29.97-30.99
7440-125	JM-QUA-40Q136SG*	4"	100	3.95"-4.15"	100.33-105.41	1.23"-1.27"	31.24-32.26
7440-130	JM-QUA-40Q136SG*	4"	100	3.95"-4.15"	100.33-105.41	1.28"-1.32"	32.51-33.53
7440-XXX		4"	100	3.95"-4.15"	100.33-105.41	CUSTOM	CUSTOM
7450-075		5"	125	4.95"-5.15"	125.73-130.81	0.73"-0.77"	18.54-19.56
7450-080		5"	125	4.95"-5.15"	125.73-130.81	0.78"-0.82"	19.81-20.83
7450-085		5"	125	4.95"-5.15"	125.73-130.81	0.83"-0.87"	21.08-22.10
7450-090		5"	125	4.95"-5.15"	125.73-130.81	0.88"-0.92"	22.35-23.37
7450-095		5"	125	4.95"-5.15"	125.73-130.81	0.93"-0.97"	23.62-24.64
7450-100		5"	125	4.95"-5.15"	125.73-130.81	0.98"-1.02"	24.89-25.91
7450-105		5"	125	4.95"-5.15"	125.73-130.81	1.03"-1.07"	26.16-27.18
7450-110		5"	125	4.95"-5.15"	125.73-130.81	1.08"-1.12"	27.43-28.45
7450-115		5"	125	4.95"-5.15"	125.73-130.81	1.13"-1.17"	28.70-29.72
7450-120	JM-QUA-50Q136SG*	5"	125	4.95"-5.15"	125.73-130.81	1.18"-1.22"	29.97-30.99
7450-125	JM-QUA-50Q136SG*	5"	125	4.95"-5.15"	125.73-130.81	1.23"-1.27"	31.24-32.26
7450-130	JM-QUA-50Q136SG* / JM-QUA-50Q142SG*	5"	125	4.95"-5.15"	125.73-130.81	1.28"-1.32"	32.51-33.53
7450-135	JM-QUA-50Q136SG* / JM-QUA-50Q142SG* / JM-QUA-50Q150SG*	5"	125	4.95"-5.15"	125.73-130.81	1.33"-1.37"	33.78-34.80
7450-140	JM-QUA-50Q142SG* / JM-QUA-50Q150SG*	5"	125	4.95"-5.15"	125.73-130.81	1.38"-1.42"	35.05-36.07
7450-145	JM-QUA-50Q150SG*	5"	125	4.95"-5.15"	125.73-130.81	1.43"-1.47"	36.32-37.34
7450-150	JM-QUA-50Q150SG* / JM-QUA-50Q167S*	5"	125	4.95"-5.15"	125.73-130.81	1.48"-1.52"	37.59-38.61
7450-155	JM-QUA-50Q167S*	5"	125	4.95"-5.15"	125.73-130.81	1.53"-1.57"	38.86-39.88
7450-160	JM-QUA-50Q167S*	5"	125	4.95"-5.15"	125.73-130.81	1.58"-1.62"	40.13-41.15
7450-165	JM-QUA-50Q167S*	5"	125	4.95"-5.15"	125.73-130.81	1.63"-1.67"	41.40-42.42
7450-170		5"	125	4.95"-5.15"	125.73-130.81	1.68"-1.72"	42.67-43.69
7450-175		5"	125	4.95"-5.15"	125.73-130.81	1.73"-1.77"	43.94-44.96
7450-180		5"	125	4.95"-5.15"	125.73-130.81	1.78"-1.82"	45.21-46.23
7450-XXX		5"	125	4.95"-5.15"	125.73-130.81	CUSTOM	CUSTOM
7460-075		6"	150	5.96"-6.15"	151.38-156.21	0.73"-0.77"	18.54-19.56
7460-080		6"	150	5.96"-6.15"	151.38-156.21	0.78"-0.82"	19.81-20.83
7460-085		6"	150	5.96"-6.15"	151.38-156.21	0.83"-0.87"	21.08-22.10
7460-090		6"	150	5.96"-6.15"	151.38-156.21	0.88"-0.92"	22.35-23.37

CABLE ACCESSORIES

L I M I T E D

SPECIFICATIONS

PRODUCT NUMBER	JACKMOON CROSS-REFERENCE NO	EACH SIZE (IN)	EACH SIZE (MM)	CONDUIT I.D. (IN)	CONDUIT I.D. (MM)	PORT DIAM RANGE (IN)	PORT DIAM RANGE (MM)
7460-095		6"	150	5.96"-6.15"	151.38-156.21	0.93"-0.97"	23.62-24.64
7460-100		6"	150	5.96"-6.15"	151.38-156.21	0.98"-1.02"	24.89-25.91
7460-105		6"	150	5.96"-6.15"	151.38-156.21	1.03"-1.07"	26.16-27.18
7460-110		6"	150	5.96"-6.15"	151.38-156.21	1.08"-1.12"	27.43-28.45
7460-115		6"	150	5.96"-6.15"	151.38-156.21	1.13"-1.17"	28.70-29.72
7460-120	JM-QUA-60Q136SG*	6"	150	5.96"-6.15"	151.38-156.21	1.18"-1.22"	29.97-30.99
7460-125	JM-QUA-60Q136SG*	6"	150	5.96"-6.15"	151.38-156.21	1.23"-1.27"	31.24-32.26
7460-130	JM-QUA-60Q136SG* / JM-QUA-60Q142SG*	6"	150	5.96"-6.15"	151.38-156.21	1.28"-1.32"	32.51-33.53
7460-135	JM-QUA-60Q136SG* / JM-QUA-60Q142SG*	6"	150	5.96"-6.15"	151.38-156.21	1.33"-1.37"	33.78-34.80
7460-140	JM-QUA-60Q142SG*	6"	150	5.96"-6.15"	151.38-156.21	1.38"-1.42"	35.05-36.07
7460-145		6"	150	5.96"-6.15"	151.38-156.21	1.43"-1.47"	36.32-37.34
7460-150	JM-QUA-60Q167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.48"-1.52"	37.59-38.61
7460-155	JM-QUA-60Q167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.53"-1.57"	38.86-39.88
7460-160	JM-QUA-60Q167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.58"-1.62"	40.13-41.15
7460-165	JM-QUA-60Q167SG*	6"	150	5.96"-6.15"	151.38-156.21	1.63"-1.67"	41.40-42.42
7460-170	JM-QUA-60Q192SG*	6"	150	5.96"-6.15"	151.38-156.21	1.68"-1.72"	42.67-43.69
7460-175	JM-QUA-60Q192SG*	6"	150	5.96"-6.15"	151.38-156.21	1.73"-1.77"	43.94-44.96
7460-180	JM-QUA-60Q192SG*	6"	150	5.96"-6.15"	151.38-156.21	1.78"-1.82"	45.21-46.23
7460-185	JM-QUA-60Q192SG*	6"	150	5.96"-6.15"	151.38-156.21	1.83"-1.87"	46.48-47.50
7460-XXX		6"	150	5.96"-6.15"	151.38-156.21	CUSTOM	CUSTOM
7480-190		8"	200	7.74"-7.94"	196.60-201.68	1.88"-1.92"	47.75-48.77
7480-195		8"	200	7.74"-7.94"	196.60-201.68	1.93"-1.97"	49.02-50.04
7480-200		8"	200	7.74"-7.94"	196.60-201.68	1.98"-2.02"	50.30-51.05
7480-205		8"	200	7.74"-7.94"	196.60-201.68	2.03"-2.07"	51.56-52.58
7480-210		8"	200	7.74"-7.94"	196.60-201.68	2.08"-2.12"	52.83-53.85
7480-215	JM-QUA-80Q238SG*	8"	200	7.74"-7.94"	196.60-201.68	2.13"-2.17"	54.10-55.12
7480-220	JM-QUA-80Q238SG*	8"	200	7.74"-7.94"	196.60-201.68	2.18"-2.22"	55.37-56.39
7480-XXX		8"	200	7.74"-7.94"	196.60-201.68	CUSTOM	CUSTOM



Cable Accessories Limited, Unit 5, Red Cow Interchange Estate, Turnpike Road, Ballymount, Dublin 22, Ireland, D22FP22



+353 1 464 1477



+353 1 464 1487



sales@cableaccessories.ie